

HICKSON DECOR WOODSTAIN

PRODUCT DESCRIPTION

Decor Wood Stain is a range of translucent finishes which will enhance the beauty of wood, allowing its natural grain to show through. All are high build, coat-on-coat products - complete finishes from a single can. They eliminate the need for a separate primer or undercoat. The highest solids content compared with alternative wood finishes provides a superior spreading capacity and also gives a greater film thickness and increased durability of the coating.

All interior and exterior softwood/hardwood applications.

- Repels water but allows wood to breathe
- Resists cracking, peeling and fading
- A complete protective finish in one can
- No primer or undercoat required
- Low maintenance

Specially formulated to provide practical advantages over alternative types of exterior finishes such as traditional paint, varnish or polyurethane, it is a complete finish in a single can, eliminating, if desired, the need for a separate primer or undercoat and providing low maintenance, long-term protection. The translucent semi-gloss finish enhances and protects the natural appearance of wood.

ideal to use on • window frames • doors • cladding • fascias • all internal and external woodwork

unique qualities • highly UV resistant • long lasting protection • water repellant • allows wood to breathe • resists flaking and peeling.

Available in

ebony, light oak, mahogany, pine pitch pine, red cedar redwood, teak.

METHODS OF APPLICATION

New timber should be well sanded, clean, non-oily and thoroughly dry. Brush apply evenly, 3 coats for exterior application or interior work, leaving 24 hours between coats.

Joinery supplied with a basecoat apply 2 brush coats leaving 24 hours between coats.

Previously stained wood should be clean. Lightly sand and apply 2 coats as required, leaving 24 hours between coats.

Old paint or varnish - strip back to bare wood, sand, clean and apply 3 coats leaving 24 hours between coats. Stir thoroughly before and during use.

A test application is recommended.

MAINTENANCE AND CLEANING

Remove dust and dirt by washing. remove loose material with a stiff brush. Mould and algae growth should be removed with a suitable fungicide. Recoat every 3-8 years as required.

Clean brushes and spillages with white spirit. Remove as much paint as possible from brush before washing. Some Local Authorities have special facilities for disposing of waste coatings. Do no empty paint into drains and watercourse. Do not use white spirit on skin. A proprietary hand cleaner should be used.

Protect from extremes of temperature during storage and application.

CAUTION

Always apply to a test area before starting work. Appearance may vary according to the colour and type of wood and the number of coats.

COVERAGE

11-18 square metres per litre, depending on substrate

DRYING TIME

Touch dry 3-5 hours. Allow 24 hours between coats.

PACKAGING

available in: 500ml, 1 litre, 2.5 litre.



STORAGE

Store in unopened containers in a cool dry place away from direct sunlight.

HEALTH SAFETY AND THE ENVIROMENT

DANGER: Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness and dizziness. Harmful to aquatic life with long lasting effects. Avoid release into the environment.

Read all instructions before use. Keep out of reach of children. Not recommended for interior use on large surface areas.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all materialhandling equipment. Contaminated cloths may self ignite without warning. Dispose of after soaking in water.

Use only in well ventilated areas. Wear protective gloves. Wear eye or face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF SWALLOWED: Immediately seek medical attention. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower, do not use solvent, thinners or white spirit. If medical advice is needed, have product container or label at hand.

Remove excess from tools and mixing vessels before cleaning with white spirits.

The information supplied herein is accurate to the best if our knowledge. Since conditions and methods are beyond our control, no warranty is expressed or implied. You are advised to assess the suitability of the product on a test area before application

Date of issue: January 2019