

Decking and Fencing Oil

one coat timber protection

DESCRIPTION

A concentrated, one coat, clear, water repellent wax coating, formulated for the protection of externally exposed timber surfaces that produces a rich professional semi-gloss finish. The grain and texture of the wood is accentuated and the timber is protected from drying out. The dried coating provides UV resistance, water droplet repellence and protection against moisture ingress, warping, swelling, cracking, and splitting, maintaining timber in a bright, clean condition.

Decking and Fencing Oil is not a varnish, its place is in the wood, not on the surface. It protects by penetrating the wood, waterproofing and enhancing the grain.

ideal to use on • decking • timber structures • exterior panelling • wood shingles • pontoons • jetties • garden furniture • picnic tables • planters • screen fencing • cladding unique qualities • water repellent

MAIN FEATURES

- Provides a highly water repellent finish
- Reduces the timber's capacity to retain water
- Unique qualities
- Water repellent. Protects against warping
- Protects against swelling. Protects against cracking
- One coat

SURFACE PREPARATION

Remove any dirt, dust, oil or grease. Surface must be dry.

New surfaces – no other preparation.

Weathered surfaces – sand down to clean, sound, treated wood (use dust mask if using sanding equipment with no dust collect on).

Previously painted or stained surfaces remove down to clean bare wood.

Decking and Fencing Oil must be absorbed into the timber.

METHODS OF APPLICATION

One liberal coat. Allow time for absorption along the grain of the timber.

By brush, short haired roller or 'vee' applicator only.

New timber should be well sanded, non-oily and thoroughly dry. Old paint, stain or varnish - strip back to bare wood, sand and clean, coat as new wood. Stir thoroughly. Do not apply below 5°C. Brush apply one coat evenly with the grain in a full flowing coat, do not overbrush. Caution: Timbers containing high natural oils, e.g. Teak and Iroko, may inhibit drying and cause impaired penetration. Wiping surface with methylated spirit will assist penetration. Wear a suitable face mask if dry sanding.

MAINTENANCE AND CLEANING

When required, every 1-2 years, depending on the level and nature of the exposure. Always remove leaves and decaying vegetation from the surface of decking as soon as possible in order to retain the benefits of Decking and Fencing Oil.

Clean brushes and spillages with white spirit. Remove as much product as possible from brush before washing. Some Local Authorities have special facilities for disposing of waste coatings. Do not empty paint into drains and watercourse. Do not empty product into drains and watercourse. Do not use white spirit on skin. A proprietary hand cleaner should be used.

Protect from extremes of temperature during storage and application.

CAUTION

Always apply to a test area before starting work. Appearance may vary according to the colour and type of wood and the number of coats.

Further information may be obtained from:

Polyvine Limited, Vine House, Cheddar Business Park, Wedmore Road, Cheddar, BS27 3EB

Tel 01934 740305 • www.polyvine.com • email info@polyvine.co.uk

COVERAGE

16-20 square metres per litre, depending on the porosity of the substrate. Due to their surface properties, ribbed or grooved as well as rough (sawn) wood surfaces absorb more product per square metre than smooth surfaces. Practical coverage can vary considerably depending on method of application, surface roughness, weather conditions and complexity of the structure.

DRYING TIME

Touch dry 12 hours. Low temperature/ high humidity can increase drying time.

PACKAGING

available in: 2.5 litre, 5 litre

STORAGE

Store unopened containers in a cool dry place away from direct sunlight.

HEALTH SAFETY AND THE ENVIRONMENT

Danger Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness and dizziness. Read label before use. Keep out of reach of children. If medical advice is needed, have the product container or label at hand. Wear protective gloves. Wear eye or face protection. This product contains max 400g/l/VOC. protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Have a well-ventilated area. Avoid release to the environment. IF INHALED: remove person to fresh air and keep comfortable for breathing. IF SWALLOWED: immediately call a POISON CENTRE or physician. Do NOT induce vomiting. IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water or shower. Keep cool. Dispose of contents and container in accordance with all local, regional, national and international regulations. May produce an allergic reaction. Repeated exposure may cause skin dryness or cracking. Hazardous ingredients.

The information supplied here is accurate to the best of our knowledge. Since conditions and methods are beyond our control, no warranty is expressed or implied. You are advised to assess the suitability of the product on a test area before application.

Date of issue: March 2023

Further information may be obtained from:

Polyvine Limited, Vine House, Cheddar Business Park, Wedmore Road, Cheddar, BS27 3EB

Tel 01934 740305 • www.polyvine.com • email info@polyvine.co.uk