

TECHNICAL DATA SHEET

ACRYLIC COLOURANT

DESCRIPTION

Super high-quality acrylic pigment specifically formulated to give superior colour saturation. Concentrated colourant can be used with water-based products. Can be used to colour Polyvine varnish and glazes.

Pigment dispersed in a mixture of surfactant, humectant, preservative and water. It does not contain Nonyl Phenol Ethoxylates as ingredients or contaminants. We recommend that this product is mixed thoroughly before use.

The pigment content is approximately 50%, the particle size is 5m.

Concentrated non-ionic and anionic dispersion of pigment.

The product has high colour strength and good compatibility with most aqueous coatings.

All colourants are intermixable to give any colour or shade.

FOR USE ON

Scumble • stain • emulsion paint • varnish and interior paint • glue • filler • masonry paint • tile grout • cement • decorative painting on walls and floors • colourwashing • dragging • graining • marbling • frottage or leather effect • stippling

AVAILABLE COLOURS

Colours available 50g: yellow, blue, green, red, crimson, yellow oxide, red oxide, prussian blue, ultramarine, magenta, emerald, lemon, violet, black, white, raw umber, burnt umber, raw sienna, burnt sienna, dark oak, mahogany, antique pine, medium oak, teak and pine

Colours available 500g: yellow, blue, green, red, yellow oxide, black, white, raw umber, burnt umber, burnt sienna, dark oak, medium oak and teak

UNIQUE SELLING POINTS

Compatible with water-based products. Can be used to colour Polyvine varnish and glazes.

Concentrated colourant can be used with water-based coatings used in the theatre, film, scenery decorative paint industry.

SURFACE PREPARATION

All surfaces must be clean and free from dust, dirt, oil/resins and contamination.

MIXING

Acrylic Colorants may be added up to a maximum of 10% by weight. But considering that it is highly concentrated, you can obtain best results by adding a minimum. The maximum additions are: 10%

Ensure product is well mixed, do not mix batch numbers.

Pour into a suitable container and mix with another colour if required.

As with all water-based coatings, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150). Or above 30°C.

TECHNICAL DATA SHEET

CAUTION

Concentrated colourant requires very small additions to vary the colour.

Test colour and mix before applying.

Always apply to a test area before starting work. Care must be taken when applying in high temperature or direct sunlight as this will affect drying time. Do not apply when rain is imminent.

COVERAGE

Dependant on base medium.

PACKAGING

50g, 500g, US 1.78oz, 17.8 oz

STORAGE

Protect from extremes of temperature during storage and application.

Store in unopened containers in a cool dry place away from direct sunlight.

Shelf Life: Many years in tightly sealed container.

HEALTH SAFETY AND THE ENVIROMENT

Non-hazardous. Keep out of reach of children. Contact with eyes - wash immediately with warm water.

If swallowed, seek medical advice immediately and show the container or label.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

CLEAN UP EQUIPMENT

Any equipment used can be cleaned using soap and water. Wipe any excess off surfaces with a damp cloth.

DISPOSAL

Look for special facilities locally. Do not empty into drains or watercourses.

TECHNICAL DATA SHEET

The information provided is prepared to the best of our current knowledge and makes no claim to be complete. The User is responsible for establishing that the product and recommendations herein are fit for the designated purpose, wood type and present situation before use. A professional and thereby successful application of the product is beyond our control. Always make a preliminary test. The User is required to read and understand all information contained on package labels and safety data sheets before using this product.

MANUFACTURED IN THE UK BY

TEL 01934 740305 **EMAIL** info@polyvine.co.uk

For technical and recycling info visit our website **polyvine.com**

EU VOC limit 130g/L 2010 (cat A/e) contains 127g/L

DATE OF ISSUE PW final 10.24 09/12/2024