

ACRYLIC ENAMEL PAINT INTERIOR – EXTERIOR

DESCRIPTION

An ultra-hard, high-quality, cross-linked acrylic, sandable coating with a gloss/satin finish.

This coating dries to a translucent coloured film with extremely good sanding properties allowing a very high quality of finish to be obtained. This product is self-extinguishing.

Polyvine Acrylic Enamel is specially formulated to bond to a wide range of surfaces.

Interior/exterior very hard and durable finish 1-2 hour drying time water resistant stain resistant heat-resistant water wash up.

For interior and exterior use, in fact, anywhere a traditional solvent-based enamel was used, these tough, durable enamels are available in a large range of intermixable colours which can be used on plastic, metal, wood, glass, ceramic, card and porcelain. Safe for children's toys. Suitable for brush or airbrush application.

FOR USE ON

Metal surfaces • laminate • timber surfaces • tile • ceramic • glass • plastics

AVAILABLE COLOURS

Gloss/satin for a shiny finish.

Metallic Gold, Metallic Silver, Metallic Copper, Baltic Blue, Brunswick Green, Black, Brown, Bright Red, Metallic Pewter, Emerald. French Blue, Fire Orange, Ferrari Red, Ivory, Lime, Midnight Blue, Metallic Black, Lemon, Leather, Orange, Pink, Purple, Sea Blue, Scarlet, Signal Green, Oak, Tan, White, Yellow, Crimson. Please check polyvine.com for what colour is available in each size.

UNIQUE SELLING POINTS

Translucent colours.

Very fast drying. Complete biocidal protection.

Quick drying - fast dry and recoat time.

Non-yellowing.

SURFACE PREPARATION

All surfaces must be clean and free from dust, dirt, oil/resins and contamination.

APPLICATION

Ensure the product is well mixed but do not shake (Inverting the container several times allows the particles to distribute evenly throughout the varnish) creating a uniform solution.

Use a Polyvine varnish synthetic brush, recommended, or by airbrush, or Gloss Roller. Roller, take care, stippling may occur, do not apply pressure this will generate air bubbles in the paint.

Thinly apply 3 coats with a Polyvine brush. On porous surfaces dilute the first coat with 10% water.

As with all water-based coatings, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150). Or above 30°C.

TECHNICAL DATA SHEET

CAUTION

Always apply to a test area before starting work. Care must be taken when applying in high temperature or direct sunlight as this will affect drying time. Do not apply when rain is imminent.

Do not continuously submerge in water. Test for compatibility before application. Not suitable for exterior bare timber.

Spills should be promptly removed. Unattended spills may cause cosmetic staining and potentially damage the surface.

Do not use on uncoated exterior timber.

Not suitable for cast iron.

COVERAGE

Coverage 15-20 sq. m per litre, 160-215 sq. ft per quart depending on the porosity of the substrate.

NUMBER OF COATS

See application section.

Cure Time: Up to 5 days @ 20°C / 70°F

Drying Time: 20 minutes

Recoat Time: 2 hours

PACKAGING

20ml, 50ml, 100ml.

STORAGE

Protect from extremes of temperature during storage and application.

Store in unopened containers in a cool dry place away from direct sunlight.

Shelf Life: Many years in tightly sealed container.

HEALTH SAFETY AND THE ENVIROMENT

Non-hazardous Keep out of reach of children. Contact with eyes - wash immediately with warm water.

If swallowed, seek medical advice immediately and show the container or label.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

CLEAN UP EQUIPMENT

Any equipment used can be cleaned using soap and water before the clear coat dries. Wipe any excess off surfaces with a damp cloth. Any dried deposits will need Polyvine Varnish and Paint Remover to remove them.

DISPOSAL

Look for special facilities locally. Do not empty into drains or watercourses.

The information provided is prepared to the best of our current knowledge and makes no claim to be complete. The User is responsible for establishing that the product and recommendations herein are fit for the designated purpose, wood type and present situation before use. A professional and thereby successful application of the product is beyond our control. Always make a preliminary test. The User is required to read and understand all information contained on package labels and safety data sheets before using this product.

MANUFACTURED IN THE UK BY

TEL 01934 740305 **EMAIL** info@polyvine.co.uk

For technical and recycling info visit our website **polyvine.com**

EU VOC limit 130g/L 2010 (cat A/e) contains 40g/L

DATE OF ISSUE PW final 10.24 04/12/2024