

ORIGINAL SCUMBLE AND TROPICAL SCUMBLE

INTERIOR – EXTERIOR

DESCRIPTION

A unique Nano-acrylic transparent glaze for decorative paint work. Dries to a durable water-resistant finish on a wide range of surfaces (test for adhesion). This interior/exterior glaze is the first water-borne product to faithfully reproduce the beauty of traditional oil finishes.

The translucency of Scumble allows multiple finishes to be achieved, giving great depth.

For use in temperatures up to 21°C (70°F).

Tropical Scumble

For use in temperatures above 21°C (70°F).

Protect with Polyvine Decorators Varnish.

Test that Scumble has cured before applying varnish.

FOR USE ON

**Decorative painting on walls and floors • colourwashing • dragging • graining • marbling
• frottage or leather effect • stippling**

AVAILABLE FINISHES

Gloss/satin for depth and a soft sheen.

Colour with Polyvine Acrylic Colourant.

UNIQUE SELLING POINTS

One hour working time • interior or exterior use • water and stain resistant • dries to a translucent finish
wash brushes and tools in water.

SURFACE PREPARATION

All surfaces must be clean and free from dust, dirt, oil/resins and contamination.

APPLICATION

Ensure the product is well mixed but do not shake (inverting the container several times allows the particles to distribute evenly throughout the product) creating a uniform solution.

Use a Polyvine varnish synthetic brush, recommended, Polyvine Original Scumble can be applied by brush, or roller. Porous surfaces should be primed with Decorators Varnish diluted 10% with water, prior to application.

Select base coat colour of Vinyl Silk Emulsion/Satin Latex or Acrylic Semi Gloss/Eggshell. Apply base coat and allow to dry for a minimum of 24 hours with ventilation. Colour Scumble with Polyvine acrylic colourants - mix thoroughly. Brush or roller the coloured scumble liberally over the basecoat. Create the desired effect by breaking the surface with crumpled rag, bag, sponge, or Polyvine tools and brushes.

TECHNICAL DATA SHEET



Applying Polyvine Original Scumble over uncured base coat will result in sissing/reticulation.

When applied over emulsion/latex paint, it is possible that Polyvine Original Scumble can draw certain stains through the paint, which were not otherwise be visible. In this case a stain sealer should be used.

As with all water-based coatings, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150). Or above 30°C.

CAUTION

Always apply to a test area before starting work. Care must be taken when applying in high temperature or direct sunlight as this will affect drying time. Do not apply when rain is imminent.

COVERAGE

Coverage 10-20 sq. m per litre, 108-215 sq. ft per quart depending on the porosity of the substrate.

NUMBER OF COATS

Reference pattern and design.

Cure Time: Up to 7 days @ 20°C / 70°F

Drying Time: Base coat - a minimum of 24 hours with ventilation.
Original Scumble - up to 24 hours.

Recoat Time: Test for dryness Minimum 24 hours. Test before applying further coats or applying protective varnish.

PACKAGING

500ml, 1L, 2L (satin and dead flat), 4L, US pint, US Quart, US gal. plastic containers.

STORAGE

Protect from extremes of temperature during storage and application.

Store in unopened containers in a cool dry place away from direct sunlight.

Shelf Life: Many years in tightly sealed container.

HEALTH SAFETY AND THE ENVIRONMENT

Non-hazardous. Keep out of reach of children. Contact with eyes - wash immediately with warm water.

If swallowed, seek medical advice immediately and show the container or label.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

CLEAN UP EQUIPMENT

Any equipment used can be cleaned using soap and water before the clear coat dries. Wipe any excess off surfaces with a damp cloth. Any dried deposits will need Polyvine Varnish and Paint Remover to remove them.

TECHNICAL DATA SHEET



DISPOSAL

Look for special facilities locally. Do not empty into drains or watercourses.

The information provided is prepared to the best of our current knowledge and makes no claim to be complete. The User is responsible for establishing that the product and recommendations herein are fit for the designated purpose, wood type and present situation before use. A professional and thereby successful application of the product is beyond our control. Always make a preliminary test. The User is required to read and understand all information contained on package labels and safety data sheets before using this product.

MANUFACTURED IN THE UK BY

TEL 01934 740305 **EMAIL** info@polyvine.co.uk

For technical and recycling info visit our website **polyvine.com**

DATE OF ISSUE PW final 10.24 09/12/2024