

CHALK PAINT MAKER

DESCRIPTION

This unique formulation turns any emulsion paint into a chalk paint when mixed together, to create a velvety smooth, chalky finish. Varnished or painted surfaces rarely needs priming, making furniture renovation simple. **ideal to use for** • vintage look • upcycling furniture • distressing • shabby chic • wood • stone • ceramic • primed metal • primed matt plastic unique qualities • velvet smooth • dead flat finish • rarely requires any surface preparation • works over old painted or varnished surfaces • covers in one coat • low odour • brushes and tools wash in water.

APPLICATION

Using one part Chalk Paint Maker to two parts matt emulsion, thoroughly mix together. All surfaces must be clean and free from dust, dirt or contaminants. Clean off any wax with white spirit. Prime bare metal and plastic. Work in exactly the same way as the instructions on your emulsion paint can. Lightly rub down between coats. For a distressed look, apply two coats of contrasting colours - when dry sand through top coat to reveal patches of base coat colour. Protect with Polyvine Chalk Paint Waxer.

COVERAGE

Exactly the same as the emulsion you have mixed it into, so please check the side of the can before you begin.

SHEEN LEVEL

The same as the emulsion, so check the side of the can before you begin.

CONTAINERS

500ml, US pint,

DRYING TIME

The same as the emulsion, so check the side of the can before you begin.

RECOAT TIME

2hrs – 4hrs

CURING

Protect the finish from water and steam for 5 Days after application

CLEANING

Clean tools/equipment with warm soapy water, rinse well with clean water, allow to dry naturally.

STORAGE

Protect from extremes of temperature during storage and application.

CAUTION.

Always apply to a test area before starting work.

Appearance may vary according to the colour and type of paint and the number of coats.

HEALTH SAFETY AND THE ENVIROMENT

Non-hazardous. Ensure good ventilation. Keep out of reach of children. Contact with eyes-wash immediately with warm water. Remove excess from tools and mixing vessels before washing in warm soapy water. Do not empty containers into drains or watercourses.

The information supplied herein is accurate to the best of our knowledge. Since conditions and methods are beyond our control, no warranty is expressed or implied. You are advised to access the suitability of the product on a test area before application.

Date of Issue: January 2019

Further information may be obtained from:

Polyvine Limited, Vine House, Cheddar Business Park, Wedmore Road, Cheddar, BS27 3EB

Tel 01934 740305 • www.polyvine.com • email info@polyvine.co.uk